

# 49 RANGER PRO



## ROTAX® ENGINE

	600R E-TEC	900 ACE
<b>Engine details</b>	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C.
<b>Cylinders</b>	2	3
<b>Displacement</b>	599.4 cc	899.0 cc
<b>Bore</b>	72,3 mm	74 mm
<b>Stroke</b>	73 mm	69.7 mm
<b>Maximum engine speed</b>	8100 RPM	7250 RPM
<b>Carburation</b>	Electronic Direct Injection	EFI
<b>Recommended fuel type</b>	Unleaded	
<b>Minimum octane</b>	95	
<b>Fuel tank</b>	37 liters	
<b>Oil tank capacity (2-stroke)</b>	3,4 liters	-

## COLOUR

Orange/Full Moon  
Silver/Black

## DIMENSIONS

<b>Vehicle overall length*</b>	3540 mm
<b>Vehicle overall width</b>	1120 mm (600R E-TEC) 1200 mm (900 ACE)
<b>Vehicle overall height</b>	1540 mm
<b>Ski stance</b>	921 mm (600R E-TEC) 996 mm (900 ACE)
<b>Track nominal width</b>	406 mm
<b>Track nominal length</b>	4141 mm
<b>Track profile height</b>	59 mm Powder Max FlexEdge

## POWERTRAIN

<b>Drive clutch type</b>	pDrive with clickers (600R E-TEC) pDrive with slide shoes (900 ACE)
<b>Driven clutch type</b>	QRS
<b>Brake system</b>	Hydraulic brake with braided steel brake line, plastic master cylinder

## SUSPENSION

<b>Front suspension</b>	LFS with bended lower A-Arms
<b>Front shock</b>	HPG 36
<b>Rear suspension</b>	EasyRide with extension lock
<b>Center shock</b>	HPG 36
<b>Rear shock</b>	HPG 36

## FEATURES

<b>Frame</b>	Radien-X	<b>Heated throttle lever</b>	Standard
<b>Skis</b>	Blade DS+	<b>Heated grips</b>	Standard
<b>Seating</b>	2-up light	<b>Gauge</b>	7.2-in. wide digital display
<b>Handlebar</b>	U-type steel with hooks, low grab handle	<b>Windshield</b>	Extra high with side deflectors
<b>Riser block height</b>	145 mm	<b>Hitch</b>	Standard
<b>Starter</b>	Electric (900 ACE) Electric and manual (600R E-TEC)	<b>Visor Plug front / rear</b>	Front
<b>Reverse</b>	RER (600R E-TEC) Mechanical (900 ACE)	<b>12V power outlet</b>	Yes, in front compartment
		<b>Air radiator with fan</b>	Yes
		<b>LinQ attachment</b>	2 pairs

\* Vehicle overall length without snowflap.