MY23 MAVERICK DS TURBO



HIGHLIGHTS

- Smart-Lok™* front differential
- FOX† 2.5 PODIUM QS3 Piggyback shocks
- High torque Dynamic Power Steering (DPS)
- 14 in. (35.6 cm) cast-aluminum wheels
- 30 in. (76.2 cm) Maxxis Carnivore† tires
- 4.5 in. (11.4 cm) digital display with keypad
- · Rear tow hook

ΕN	GI	N	Е
----	----	---	---

Туре	101 kW (135 hp), Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled and high- perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L $/$ H $/$ N $/$ R $/$ P
Drive Train	Lockable front differential with exclusive Smart-Lok* technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL *Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry
Power Steering	High torque Tri-Mode Dynamic Power Steering

SUSPENSIONS

Front Suspension	Double A-arm with sway bar / 20 in. (50.8 cm) travel
Front Shocks	FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar / 20 in. (50.8 cm) travel
Rear Shocks	FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment and bottom-out control
TIRES / WHEELS	

Front & Rear Tires	Maxxis Carnivore† 30 x 10 / 10 x 14 in. (76.2 x 25.4 / 25.4 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum

BRAKES

Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm disc brakes with hydraulic twin-piston calipers

DIMENSIONS / CAPACITIES

Estimated Dry Weight *	1,546 lb (701.3 kg)
Chassis / Cage	Dual-phase 980 steel
LxWxH	132 x 64 x 65.4 in. (335.3 x 162.5 x 166.1 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	14 in. (35.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L)
Fuel Capacity	10.5 gal (40 L)

FEATURES

Gauge	4.5 in. (11.4 cm) wide digital display with
	keypad
Instrumentation	DC Outlet (10-A)
Magneto	650 W
Ingnition	RF Digitally Encoded Security System
	(D.E.S.S.™) with Start / Stop button
Lighting	LED headlights
	LED tail lights
Winch	N/A
Protection	Integrated front bumper
	Quarter-doors
	HMWPE full skid plate
	Rear tow hook

WARRANTY

F	o DDD II ii i
Factory warranty	2-year BRP limited warranty



