2023

RENEGADE X-RS

A hard-charging, race-inspired machine with the most advanced features and technology.



RENEGADE X-RS 850 E-TEC SHOWN

// WHAT'S NEW

- REV® Gen5 platform (850 E-TEC® only)
- 10.25" color touchscreen display with BRP Connect available (850 E-TEC only)
- Smart-Shox™ semi-active suspension available with Pilot™ X skis
- Premium LED headlights

// PACKAGE HIGHLIGHTS

- Rotax® 850 E-TEC and 900 ACE™ Turbo R engines available
- High-performance KYB† Pro shock package
- 7.8 in. wide LCD display with BRP Connect available
- RAS[™] X front suspension

- rMotion™ X rear suspension
- Electric starter
- RS running boards
- pDrive™ clutch
- Forward steering post position (850 E-TEC)
- Rack steering system
- Forward adjustable riser
- Transparent handguards
- Open toe-hold
- · Backlit multifunction handlebar controls

| ROTAX ENGINE | 850 E-TEC | 900 ACE TURBO R |
|-------------------------------|---|--|
| Engine details | Liquid-cooled, two-stroke, eRAVE™ | Liquid-cooled, four-stroke D.O.H.C., dry sump, turbocharged |
| Cylinders - Displacement | 2 - 849 cc | 3 - 899 cc |
| Bore - Stroke (mm) | 82 - 80.4 | 73 – 69.7 |
| Carburation | E-TEC direct injection with additional booster injectors | EFI |
| Fuel type – Octane | Unleaded – 95 | Unleaded – 95 |
| Fuel tank (L/US gal) | 36/9.5 | 36/9.5 |
| Oil tank capacity (L/qt) | 3.4/3.6 | 3.3/3.5 |
| POWERTRAIN | | |
| Drive clutch Driven clutch | pDrive with clickers QRS Vent | pDrive QRS Vent |
| Drive sprocket pitch | 73 mm/2.86 in. | 73 mm/2.86 in. |

| DIMENSIONS | | |
|-------------------------------------|---|--|
| Overall vehicle length | 3,038 mm/119.6 in. | |
| Overall vehicle width | 1,209 - 1,232 - 1,255 mm/47.6 - 48.5 - 49.4 in. | |
| Overall vehicle height | 1,222 mm/48.1 in. | |
| Ski stance | 1,092 mm/43 in. adjustable | |
| Track (Length x Width x Profile) | lce Ripper† XT: 137 x 15 x 1 5 in | |

COLOR

Platinum Silver / Spartan Red
Black

| Front suspension | RAS X |
|-------------------------|---|
| Front shock | KYB Pro 36 EA-3 (REV Gen5) KYB Pro 36 EA (REV Gen4) KYB Pro Smart-Shox opt. |
| Front suspension travel | 265 mm/10.4 in. |
| Rear suspension | rMotion X |
| Center shock | KYB Pro 40 EA-3 (REV Gen5) KYB Pro 40 EA (REV Gen4) |
| Rear shock | KYB Pro 40 EA-3 (REV Gen5) KYB Pro 40 EA (REV Gen4) KYB Pro Smart-Shox opt. |
| Rear suspension travel | 292 mm/11.5 in. |

FEATURES

| . =/(: • !(= • | |
|-----------------------------|--|
| Platform | REV Gen5 (850 E-TEC only) REV Gen4 |
| Skis | Pilot X |
| Seating | Trail performance (2-stroke engines) Trail with storage (4-stroke engines) |
| Handlebar | U-shaped aluminum with J-hooks/ Transparent handguards |
| Riser block height | Adjustable 120 mm/4.7 in. |
| Starter | Electric |
| Reverse | RER™ (850 E-TEC) |
| | Electro-mechanical (900 ACE Turbo R) |
| Brake system | Brembo [†] |
| Heated throttle lever/grips | Standard |
| Gauge type | 7.2 in. digital display |
| | 7.8 in. wide LCD color (opt. 900 ACE |
| | Turbo R) |
| | 10.25 in. touchscreen (opt. 850 E-TEC) |
| Windshield | Optional |
| Runner - Carbide | Round 1/2 – 4 in. |
| Bumpers (front/rear) | Std/Std |

ski-doo.

